Wheel Days 2019 Demolition Derby

Superintendent: Michael Haines/John Curtis (315) 922-8899/ (607) 244-2161

MINI-VANS & TRUCK RULES

TRUCKS & VANS MUST REMAIN STOCK UNLESS OTHERWISE NOTED.

- 1. Derby is open to ½ ton, ¾ ton, or 1ton trucks only (NO 4x4's- four wheel drive chassis must have one drive shaft removed).
- 2. BODY- All vehicles must be stripped of all glass, chrome, trim, side mirrors, and plastic and fiberglass panels. **Windshields are NOT acceptable**. Rubber body mounts may be removed, but must be replaced with flat washers. No hood latches. ** 2 STEEL BARS MUST BE MOUNTED FROM THE FIRE WALL TO ROOF**.
- 3. GAS TANKS- Must be in center of bed near cab, securely fastened down and covered with metal shield. VANS tank may be moved inside, secured and covered.
- 4. FRAME- No alterations or reinforcements to frame. Box can be welded to cab 3" every 10".
- 5. TRANSMISSION- Floor shifters are allowed.
- 6. BRAKES- All vehicles must have and will be checked for brakes and air cleaner.
- 7. BUMPERS- May be welded or chained whatever it takes to keep them on the vehicle. Bumper can be car style, but must remain stock height.
- 8. REAR ENDS- May be welded. No coil to leaf-spring alteration.
- 9. DOORS- Must be chained, wired, OR welded (2" 3" weld on each door) every 10". No full welded seams except driver door.
- 10. DRIVER COMPARTMENT- One cross bar is allowed behind the seat running door to door. This is to keep from caving in maximum diameter is 3".
- 11. EXHAUST- Must extend beyond driver's seat or you may run stacks.
- 12. FAN BLADES- Must be clutch type with shroud OR electric fan OR no fan at all.
- 13. FENDERS & INNER- Cutting, folding, or bending is permitted.
- 14. HOOD & TRUNK- All hoods can be wired, OR chained down, and must have an 18" hole in it. Trunk lids must be wired, chained, OR welded 3" for every 10". No hood latches.
- 15. SUSPENSION- Truck should be stock range. NO MODIFICATION OF SUSPENSION.

- 16. BATTERY- May be left under hood or moved to passenger side floor (must be held down by 2 straps and covered with rubber mat).
- 17. TIRES- Max 15" (16" only if factory). Inner tubes are allowed. Wheel weights must be removed.
- 18. ANTI-FREEZE- NOT allowed only clear water. If seen, you will be disqualified. Flush motor block with water.
- 19. All contestants will have one minute to restart and/or make contact with a live car. NO TRAPPING WILL BE ALLOWED.